

Benchmark[®] 205-LV2 Hot Melt System

The Smartest, Surest Way To Get Started In Hot Melts.

Those who are looking to move up from staplers, stick guns or cold glue systems to hot melts can find no better way to start than with Hot Melt Technologies (HMT), Benchmark 205-LV2 System.

Proven in thousands of low- and medium-volume applications, affordably priced and now 30% more powerful, the Benchmark 205-LV2 System is:

Pre-Assembled And Ready To Run

Load the Benchmark 205-LV2 with adhesive, plug it into a 120-volt outlet, turn it on, and in 30 minutes you're ready to go.

Ideal For Product Assembly or Packaging

The Benchmark 205-LV2 dispenses adhesives in bead or spray patterns through one or two handguns.

Built Tough For Dependability

Designed for rugged, shop-floor conditions, the Benchmark 205-LV2 features a sealed fractional HP drive motor, a cast iron pump with steel spur gears, high-strength heated hoses, and steel gun nozzles.

Easy To Operate And Maintain

Put down the instruction manual and switch on the power button; the Benchmark 205-LV2 is designed for easy operation and ready serviceability.



**Hot Melt
Technologies, Inc.**
No One Puts It Together Like HMT.

Benchmark[®] 205-LV2 Hot Melt System

The Affordable Hot Melt System
That's Now 30% More Powerful!

Benchmark 205-LV2

Perfect for low- and medium-volume product assembly and packaging applications, the HMT Benchmark[®] 205-LV2 Hot Melt System is an affordable alternative to staplers, stick guns or cold glue systems.



SPECIFICATIONS

Tank Capacity

- 1.125 Gallons (4.26 liters)
Approx. 8 lbs*

Number of Hoses/Guns

- 2 hoses/handguns (with bead nozzles)
- 1 hose/handgun (with spray nozzle)

Hose Lengths

- 8, 12 or 16 feet

Handgun Configuration

- Standard Entry
- Top Entry
- In-Line Entry

Electrical

- 120 vac, 15 amp

Drive Motor

- Electric, fractional HP

Pump

- Cast iron with steel gears

Viscosity

- Up to 10,000 cps

Flow Control

- Up to 50 lbs. per hour*

Melt Rate

- Up to 10 lbs. per hour*

Temperature Control

- Dial-adjustable from 250° F to 375° F

Dimensions

- 11" x 24" x 18" high (approx. 50 lbs.)

Warranty

- One-yr. limited warranty

Accessories

- Overhead Hose Boom & Balancer
- Steel Cart With Castors
- On-Off Timer: 24-hr/7-day

Applications

- Case and carton sealing
- Woodworking
- Foam laminating
- General product assembly

* Rates will vary depending on adhesive type and viscosity.

From HMT – An Industry Leader

Hot Melt Technologies has been a leader in the hot melt applications industry since 1981. We offer the applicators, accessories and adhesives you need to become efficient, all from a single source. And, we provide the after-purchase support you need to stay productive, job after job after job.

So, if you're seeking value, convenience and satisfaction, remember, No One Puts It Together Like HMT.



**Hot Melt
Technologies, Inc.**

No One Puts It Together Like HMT.

1723 West Hamlin Road • P. O. Box 80067 • Rochester, Michigan 48308

Tel: 248-853-2011 • Fax: 248-853-6650 • Web: www.hotmelt-tech.com

ISO 9001 – INTERNATIONAL QUALITY ASSURANCE STANDARD

©2003 Hot Melt Technologies, Inc. 5/05