

# Benchmark<sup>®</sup> 215-HV Hot Melt System

## It's Time To Step Up To A Benchmark<sup>®</sup> 215-HV.

Should you choose a hot melt system with a small melt tank – or a large one? A low-cost, low-volume unit ... or a higher-volume system that can accommodate future growth?

The Benchmark 215-HV System from Hot Melt Technologies (HMT<sup>®</sup>;) simplifies your decision-making process. With its 15-lb. tank, high-output pump, and one or two-gun capacity, it's ready to work for you now ... and in the future.

Offering an excellent performance-to-price ratio, the Benchmark 215-HV is:

### Pre-Assembled And Easy To Set-up

Plug the Benchmark 215-HV in to a 120-volt outlet, load it with adhesive and turn on the power. In just 30 minutes you're ready to start gluing.

### Built Tough For Years Of Dependability

The Benchmark 215-HV includes a sealed, fractional-HP drive motor and cast aluminum melt tank. It also features a "cool touch" fiberglass shroud and high-strength hoses along with a gun (or guns) with steel nozzles.

### Easy To Operate With Tamper-Resistant Controls

Simply dial in the temperature for the tank, hoses and gun(s). Then, secure the front access panel to keep meddling fingers out! The system monitors temperatures and helps assure safe operation.



**Hot Melt  
Technologies, Inc.**  
No One Puts It Together Like HMT<sup>®</sup>.

# Benchmark<sup>®</sup> 215-HV Hot Melt System

An Affordable Hot Melt System With The Power To Meet Your Needs.

## Benchmark 215-HV

The Benchmark<sup>®</sup> 215-HV Hot Melt System is perfect for medium- to high- volume product assembly and packaging applications. And, given HMT's reputation for quality, durability and performance, it's a system you can install with confidence.



## From HMT – An Industry Leader

Hot Melt Technologies has been a leader in the hot melt applications industry since 1981. We offer the applicators, accessories and adhesives you need to become efficient, all from a single source. And, we provide the after-purchase support you need to stay productive, job after job after job.

So, if you're seeking value, convenience and satisfaction, remember, No One Puts It Together Like HMT.



## Hot Melt Technologies, Inc.

No One Puts It Together Like HMT.

1723 West Hamlin Road • P. O. Box 80067 • Rochester, Michigan 48308  
Tel: 248-853-2011 • Fax: 248-853-6650 • Web: [www.hotmelt-tech.com](http://www.hotmelt-tech.com)  
**ISO 9001 – INTERNATIONAL QUALITY ASSURANCE STANDARD**

©2005 Hot Melt Technologies, Inc. 5/05

## SPECIFICATIONS

### Tank Capacity

- 1.85 Gallons. (7 Liters)  
Approx. 15 lbs.\*

### Number of Hoses/Guns

- 2 hoses/handguns

### Hose Lengths

- 8, 12 or 16 feet

### Handgun Configuration

- Standard Entry
- Top Entry
- In-Line Entry

### Electrical

- 120 vac, 15 amp

### Drive Motor

- All-electric, fractional HP

### Pump

- Cast iron with steel gears

### Viscosity

- Up to 10,000 cps

### Flow Control

- Up to 60 lbs. per hour\*

### Melt Rate

- Up to 12 lbs. per hour\*

### Temperature Control

- Dial-adjustable from 250° F to 375° F

### Dimensions

- 11" x 24" x 23" high (approx. 60 lbs.)

### Warranty

- One-yr. limited warranty

### Accessories

- Overhead Hose Boom & Balancer
- Steel Cart With Castors
- On-Off Timer: 24-hr/7-day
- Shot Timer & Foot Switch
- Automatic Guns
- Guns Nozzles: Bead or Spray, interchangeable

### Applications

- Case and carton sealing
- Woodworking
- Foam laminating
- Product assembly

\* Rates will vary depending on adhesive type and viscosity.