

System	Benchmark 205-LV	Benchmark 215-HV	Benchmark 215-HVR
Melt Tank Capacity	8 lbs.	13 lbs.	13 lbs.
Temperature Control	225 to 400°F ± 1 Microprocessor controlled	225 to 400°F ± 1 Microprocessor controlled	100 to 425°F ± 1 Microprocessor controlled
Melt Rate	Up to 10 lbs./hour	Up to 12 lbs./hour	Up to 12 lbs./hour
Flow Rate	Up to 50 lbs./hour	Up to 50 lbs./hour	Up to 60 lbs./hour
Viscosity	Up to 10,000 cP	Up to 10,000 cP	Up to 10,000 cP
Max Number of Hoses/Guns	2 Hoses / 2 Guns	2 Hoses / 2 Guns	1 Hose / 1 Gun
Hose Lengths	8, 12, or 16 feet	8, 12, or 16 feet	6, 8, 12, 16, or 20 feet
Guns	Handguns For Bead Applications	Handguns For Bead Applications	Handguns Automatic Guns For Bead or Spray Applications
Electrical	120vac, 20amp	120vac, 20amp	120vac or 220vac, 20amp
Drive Motor	Electric, fractional HP	Electric, fractional HP	Electric, fractional HP
Pump	Cast iron with steel gears	Cast iron with steel gears	Cast iron with steel gears
Dimensions	11" W x 23" L x 17" H	11" W x 23" L x 21" H	11" W x 23" L x 21" H
Shipping Wt. (approx.)	70 lbs.	70 lbs.	80 lbs.
System Control Features	Digital Run Temp Display, °F or °C Digital Set Point Display Safety Set-Lock Auto-Off Fault Detection	Digital Run Temp Display, °F or °C Digital Set Point Display Safety Set-Lock Auto-Off Fault Detection	Digital Run Temp Display, °F or °C Digital Set Point Display Safety Set-Lock Manual Standby Temp Set Back Auto-Standby/Auto-Off Timer System Ready Output
Warranty	HMT One-Year Limited Warrenty	HMT One-Year Limited Warrenty	HMT One-Year Limited Warrenty
Applications	Case and carton sealing Foam Assembly General product assembly Drawer Bottom and Cabinet Backs	Case and carton sealing Foam Assembly General product assembly Drawer Bottom and Cabinet Backs	Case and carton sealing Foam Assembly General product assembly Drawer Bottom and Cabinet Backs