# SAFETY DATA SHEET



# 1. Product and Company Identification

Product Name: HMT 6410 Hot Melt Technologies, Inc. 1723 W Hamlin Road Rochester Hills, MI 48309 For additional emergency, health, safety, or regulatory information, call 248-853-2011 during business hours.

Product Use: Hot melt adhesive for tape, tag and label Not recommended for: structural applications.

### 2. Hazards Identification

#### **GHS Ratings:**

There are no GHS ratings that apply to this product at this time

#### **GHS Hazards**

There are no GHS hazards that apply to this product at this time

### **GHS Precautions**

P103 Read label before use

P281 Use personal protective equipment as required

P302 IF MOLTEN MATERIAL ON SKIN: Immediately immerse in or flush with large

amounts of of cool water to dissipate heat. Do not try to remove adhesive. Cover with

clean cotton and get prompt medical attention

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing

P308+P313 IF exposed or concerned: Get medical advice/attention P332+P313 If skin irritation occurs: Get medical advice/attention

### 3. Composition Information on Ingredients

\*Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) See Section 8 for exposure limit guidelines.

\* Ingredient Disclosure List (IDL). All ingredients in this product are listed on the Domestic Substance List (DSL).

Chemical Name	CAS number	Weight Concentration %
Distillates (petroleum), hydrotreated heavy napthenic	64742-52-5	

4/1/2023

#### 4. First Aid Measures

Inhalation: Not likely. Move victim to fresh air if needed.

**Eye Contact:** For material in supplied state - immediately flush eyes with plenty of water for at least 15 minutes-occasionally lift eyelids. Call a physician if irritation persists.

**Skin Contact:** For contact with material as supplied- wash with soap and and water. For molten adhesive - immediately immerse in or flush with large amounts of cold water to dissipate heat. Cover with clean cotton and get prompt medical attention.

**Ingestion:** Not likely in normal use. If swallowed, do not induce vomiting. Give 2 glasses of water (16oz.) and contact a physician.

**Notes to Physician:** Product in original form should pose no hazard. Material is heated to apply. Molten material may cause burns.

# 5. Firefighting Measures

Flash Point: Not determined

LEL: N/A UEL: N/A

Flammable Limits: Not established

Extinguishing Media: Water spray of fog, CO2, or dry chemical. Use care not to splash adhesive.

Unusual Fire and Explosion Hazards: Material will burn in a fire.

Hazardous Combustion Products: None hazardous. Carbon dioxide, carbon monoxide and various

hydrocarbons.

**Firefighting::** Wear self-contained breathing apparatus.

Fire Equipment: Wear self-contained breathing apparatus. Keep containers cool to prevent rupture.

## 6. Accidental Release Procedures

**Spillage**: Ensure that all clean-up personnel wear all appropriate protective equipment. Do not allow material to get into sewer or waterway.

Small Spills: Sweep or vacuum materials. Dispose in trash.

Large Spills: Sweep or vacuum materials. Dispose of as non hazardous waste.

### 7. Handling and Storage

Handling: Routine housekeeping should be in place to assure that material does not accumulate on surfaces.

Clean up small spills.

**Storage Requirements**: Normal storage temperatures in a dry warehouse.

Regulatory Requirements: During hot processing air removal or air flow may be necessary.

# 8. Exposure Control and Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits	
Distillates (petroleum),	Not Established	Not Established	Not Established	
hydrotreated heavy napthenic				
64742-52-5				

2

Engineering Controls: Ventilation should be sufficient to control airborne levels/fumes.

**Ventilation:** Use in a properly ventilated area.

4/1/2023

**Administrative Controls:** Use good personal hygiene when handing this product. Wash hands after use, before smoking, eating, or using the toilet.

**Protective Gear:** Wear safety glasses near extrusion and fill points. Wear heat resistant gloves when working near molten material.

Contaminated Gear: Use care if molten material is on gear. Do not try to remove until it has cooled.

# 9. Physical and Chemical Properties

Properties are supplied for safety, health and environmental considerations and may not fully represent product specifications.

Specific Gravity 0.98

Freezing point: Not applicable

Boiling range: Not determined

Evaporation rate: Not determined

Explosive Limits: Not determined

Autoignition temperature: Not determined

Viscosity: 3,200 - 4,400 cps

@325°F

Appearance: Clear to brownish in

color, solid pillow

Vapor Pressure: Not determined

Vapor Density: Not determined

Melting point: 170°F

Solubility: Insoluble in water

Flash point: Not determined

Flammability: Not determined

Partition coefficient (n- Not determined

octanol/water):

Decomposition temperature: Not determined

VOC: Not applicable

Odor: Characteristic odor of

resin

Odor threshold: Not determined

pH: Not applicable

### 10. Stability and Reactivity

### **Stability:**

STABLE

**Incompatible Materials:** 

## **Hazardous Decomposition Products:**

Hazardous polymerization will not occur.

#### 11. Toxicological Information

Mixture Toxicity
Component Toxicity

64742-52-5 Distillates (pe

Distillates (petroleum), hydrotreated heavy napthenic

Oral LD50: 5,000 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Rabbit)

**Toxicity**: Information appears only if there are issues that need to be considered.

**Routes of Entry:** Material in furnished state does not pose any hazards.

**Target Organs:** Exposure to this material may affect the following organs:

3 4/1/2023

Skin: Contact with molten material can cause burns.

Eyes: Vapors from molten product might cause eye irritation.

**Respiratory System:** Vapors from molten product might cause nose irritation.

#### **Effects of Overexposure**

Carcinogenicity: None

<u>CAS Number</u> <u>Description</u> <u>% Weight</u> <u>Carcinogen Rating</u>

64742-52-5 Distillates (petroleum), hydrotreated Distillates (petroleum),

heavy napthenic hydrotreated heavy napthenic: EU

REACH: Present (L)

Acute Toxicity: None

Conditions Aggravated: Hot fumes may cause eye, skin or respiratory irritations

Chronic Effects: None known.

# 12. Ecological Information

**Ecological:** Any information available follows.

**Component Ecotoxicity** 

Distillates (petroleum), LC50 96 h Oncorhynchus mykiss >5000 mg/L (IUCLID) hydrotreated heavy napthenic EC50 48 h Daphnia magna >1000 mg/L (IUCLID)

## 13. Disposal Considerations

**Disposal**: Reclaim if feasible. If disposal is required, dispose of material and waste in a sanitary landfill or incinerate in an industrial, commercial, or municipal incinerator.

### 14. Transport Information

**Transportation Instructions:** The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

Agency	Proper Shipping Name	<u>UN Number</u>	Packing Group	<b>Hazard Class</b>
DOT	Not regulated			

IATA Not regulated

### 15. Regulatory Information

The following information is provided based upon the best information at our disposal.

This product does not contain any chemicals subject to Proposition 65.

Country Regulation All Components Listed

4 4/1/2023

#### **EU Risk Phrases**

R33: Danger of cumulative effects

#### **Safety Phrase**

S36: Wear suitable protective clothing

All components of this product are on the TSCA Inventory or are exempt from TSCA requirements. This product is not considered hazardous according to regulatory guide lines.


### SARA Title III.

Product Classification under SARA 311: Acute (no), Fire (no), Reactive (no), Pressure (no). Product Classification under SARA 355: This product contains no extremely hazardous substances.

### 16. Other Information

### **Hazardous Material Information System (HMIS)**

### **National Fire Protection Association (NFPA)**



DISCLAIMER - The warranty, as stated above, supersedes all other warranties, express or implied. Hot Melt Technologies expressly disclaims any other warranties, including warranties of merchantability and fitness for a particular purpose. Hot Melt Technologies' acceptance of purchaser's order for this product is expressly conditional on purchaser's assent to terms and conditions set forth herein. Regardless of whether Hot Melt Technologies suggested the product or developed the product at the purchaser's request, it is the purchaser's responsibility to test and determine the suitability of the product for the purchaser's intended use and purpose, and purchaser assumes all risk and liability whatsoever.

We believe the information included on this Material Safety Data Sheet to be correct, to the best of our knowledge. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that tests be made in a laboratory or plant to determine if this product meets all of your requirements. It is the responsibility of the buyer/user to determine the suitability of this product for his/her application/requirements.

5 4/1/2023