



PROFLEX® HD G6


Grid-Melter System, HD Display
240V, 3ph

Standard Features

- ▶ High-Definition Display
- ▶ Integrated 24/7 Timer
- ▶ Auto-Standby
- ▶ Auto-Off Timer
- ▶ Ready Delay Timer
- ▶ Manual Standby
- ▶ All Zone Ready
- ▶ Set Point Limit
- ▶ Set Lock
- ▶ Language Select: En, Sp, Fr
- ▶ Temp Readout, °F or °C
- ▶ ±1°F Temp Control
- ▶ Hose/Gun On/Off Control
- ▶ Up to 2 Hose/Gun Capability
- ▶ Audible Fault Alarm
- ▶ Service Clock
- ▶ Pump On/Off Control
- ▶ Precision Flow Control
- ▶ Hinged Lid

Common Options

- ▶ #340-032 Key Lock
- ▶ #921-014 Steel Cart Assembly
- ▶ #921-017 Base Cart
- ▶ #XP-922-221 OEM Interface Cable
- ▶ #XP-922-040 Remote Motor Run Cable
- ▶ Load Alert
- ▶ #934-112 Modbus, 2-Way Communication



System Configuration 220V, 40 amp, 3ph

G6	XXX	-	W	-	XHD	-	X	-	3P
CONTROL PACKAGE	TANK SIZE	TANK HEATER HARNESS	MOTOR	PA-50 PUMP	VOLTAGE				
	135 lb 		 CONSTANT SPEED F - 113 RPM, 1/3 HP K - 170 RPM, 1/3 HP	SINGLE "1"	240V, 3ph "3P"				
	200 lb 		 VARIABLE SPEED A - AC 0-125 RPM	Dual "2"					

Effective Date: 05/21/2026
All prices are subject to change without notice